

# MATERIAL SAFETY DATA SHEET

PRODUCT NAME: AB CARPET PRESpray & SPOTTER  
PRODUCT CODE: B19 (formerly 2610)  
PRODUCT CLASS: LIQUID CLEANING COMPOUND

RATINGS:  
4-EXTREME  
3 SERIOUS  
2-SIGNIFICANT  
1-SLIGHT  
0-MINIMUM

HMIS HAZARD RATING:	
HEALTH	1
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION:	B

## SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CELLO PROFESSIONAL PRODUCTS  
ADDRESS : 1354 Old Post Road , Havre de Grace, MD 21078  
EMERGENCY PHONE – INFOTRAC 24 HOURS: 800-535-5053  
INFORMATION PHONE: 800-638-4850

REVISED: 7/1/06

## SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg	@ TEMP	WEIGHT PERCENT
* ETHYLENE GLYCOL MONOBUTYL ETHER PEL 25ppm;120mg/m3 TWA (8 Hr.) SKIN TLV 25ppm;121mg/m3 TWA (8 Hr.) SKIN	111-76-2	.6	20°C	5.00

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

# Indicates hazardous chemical(s) subject to the reporting requirements of section 312 of Title III and of 40 CFR 370.

## SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: 212°F  
VAPOR DENSITY: Heavier than air  
EVAPORATION RATE: Slower than water  
APPEARANCE: Golden yellow liquid  
pH: 9.8 ± 0.2

SPECIFIC GRAVITY (H2O=1): 1.05  
VAPOR PRESSURE: Not Determined  
SOLUBILITY IN WATER: Completely  
ODOR: Citrus orange  
VOLATILE : 87.68%

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT: None  
FLASH METHOD: SETA FLASH  
FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.1 UPPER: 10.6  
EXTINGUISHING MEDIA: IF INVOLVED IN A FIRE USE FOAM, CO2 OR WATER FOG  
SPECIAL FIREFIGHTING PROCEDURES: Spray water on cartons involved in fire to keep them from igniting. Wear self-contained breathing apparatus due to the possible toxic fumes from plastic containers and or the vaporization of potentially harmful chemicals. (See section II)  
UNUSUAL FIRE AND EXPLOSION HAZARDS: Area will become slippery if material is released.

## SECTION V - REACTIVITY DATA

STABILITY: Stable  
CONDITIONS TO AVOID: Extreme heat or freezing temperatures.  
INCOMPATIBILITY (MATERIALS TO AVOID): Acids, strong alkalis and oxidants.  
HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Normal products of combustion-carbon dioxide and carbon monoxide  
HAZARDOUS POLYMERIZATION: Will not occur

## SECTION VI - HEALTH HAZARD DATA

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Not considered a hazard  
SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Can cause irritation to eyes, causing corneal damage. Can also cause skin irritation and defatting with long term exposure.  
SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: No effects of exposure expected due to absorption or contact. May possibly cause irritation or dermatitis in some individuals upon prolonged contact.  
INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE: Single dose ingestions are not considered hazardous. Extremely large doses could cause injury.  
HEALTH HAZARDS (ACUTE AND CHRONIC): Will cause only slight irritation of skin regardless of extent or exposure  
CARCINOGENICITY: NTP CARCINOGEN: No IARC MONOGRAPHS: No OSHA REGULATED: No NOT LISTED  
MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: Existing dermatological conditions may be aggravated by overexposure.  
EMERGENCY AND FIRST AID PROCEDURES:  
IF IN EYES: Immediately flush with plenty of warm water for 15 minutes while keeping eyelids apart for maximum irrigation. If irritation persists contact physician.  
IF ON SKIN: Wash off with large amounts of soap and water. If irritation persists contact a physician. Wash contaminated clothing before re-use.  
IF INHALED: If victim complains of headache, dizziness or nausea, remove victim to fresh air. If breathing becomes difficult or condition persists, contact a physician.  
IF INGESTED: Drink no more than 2 glasses of water and induce vomiting. Never give anything by mouth to an unconscious victim. Seek medical attention

## SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Dike area to contain material. Area may become slippery. Absorb product onto porous material such as sand, diatomaceous earth or commercial absorbent material. Shovel up into leak proof containers.  
WASTE DISPOSAL METHOD: Consult local, state and or federal authorities for proper disposal.  
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Do not store near acids, oxidizers, alkalies and base metals. Keep from excessive heat and keep from freezing. Do not store near consumables. Keep out of reach of children.  
OTHER PRECAUTIONS: Read and follow all directions. Use in a manner consistent with product intent.

## SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: None needed for normal use  
VENTILATION: Normal ventilation adequate  
PROTECTIVE GLOVES: Chemical resistant gloves recommended.  
EYE PROTECTION: Safety splash goggles recommended.  
OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Source of water for washing is recommended.  
WORK/HYGIENIC PRACTICES: Wash hands after use and before eating, drinking, or smoking. Remove contaminated clothing and wash before reuse.

## SECTION IX - REGULATORY INFORMATION

ALL INGREDIENTS OF THIS PRODUCT ARE LISTED ON THE US TOXIC SUBSTANCE CONTROL ACT (TSCA) INVENTORY.

This product is not a DOT hazardous material. BILL OF LADING (all sizes): "Compound, cleaning and/or polishing"

The ingredients from Section II are subject to the following reporting requirements:

MA - The Massachusetts Hazardous Substance List NJ - The New Jersey Right-to-Know Hazardous Substance List PA - The Pennsylvania Hazardous Substance List

## SECTION X - DISCLAIMER

The information contained herein has been developed based upon current available scientific data. New information may be developed from time to time which may render the conclusions of this report obsolete. Therefore, no warranty is extended or implied as to the applicability of this information to the users intended purpose or for the consequences of its use or misuse.