

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: HARDWOOD FLOOR CLEANER
PRODUCT CODE: Z79 (formerly 1331)
PRODUCT CLASS:

RATINGS:
4-EXTREME
3 SERIOUS
2-SIGNIFICANT
1-SLIGHT
0-MINIMUM

HMIS HAZARD RATING:	
HEALTH	3
FLAMMABILITY	0
REACTIVITY	0
PERSONAL PROTECTION:	

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME: CELLO PROFESSIONAL PRODUCTS
ADDRESS : 1354 Old Post Road , Havre de Grace, MD 21078
EMERGENCY PHONE - INFOTRAC 24 HOURS: 800-535-5053
INFORMATION PHONE: 800-638-4850

REVISED: 7/1/06

SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS

REPORTABLE COMPONENTS	CAS NUMBER	VAPOR PRESSURE mm Hg	@ TEMP	WEIGHT PERCENT
Nonylphenoxypoly(ethoxy)ethanol ACGIH TLV N/A OSHA PEL N/A	9016-45-9			1

Section 3 -- HAZARDS IDENTIFICATION

ROUTES OF EXPOSURE: INHALATION of vapor or spray mist. EYE or SKIN contact with the product, vapor or spray mist.
EFFECTS OF OVEREXPOSURE: EYES: Irritation. SKIN: Prolonged or repeated exposure may cause irritation. INHALATION: Irritation of the upper respiratory system.
SIGNS AND SYMPTOMS OF OVEREXPOSURE: Redness and itching or burning sensation may indicate eye or excessive skin exposure.
MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: None generally recognized.
CANCER INFORMATION: For complete discussion of toxicology data refer to Section 11.

Section 4 -- FIRST AID MEASURES

EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention. **SKIN:** Wash affected area thoroughly with soap and water. **INHALATION:** If affected, remove from exposure. Restore breathing. Keep warm and quiet. **INGESTION:** Do not induce vomiting. Get medical attention immediately.

Section 5 -- FIRE FIGHTING MEASURES

FLASH POINT: >200°F PMCC **LEL:** N.A. **UEL:** N.A. **FLAMMABILITY CLASSIFICATION:** N/A

EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Alcohol Foam

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode (due to the build-up of pressure) when exposed to extreme heat. During emergency conditions overexposure to decomposition products may cause a health hazard. Symptoms may not be immediately apparent. Obtain medical attention.

SPECIAL FIRE FIGHTING PROCEDURES: Full protective equipment including self-contained breathing apparatus should be used. Water spray may be ineffective. If water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Section 6 -- ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition. Ventilate the area. Remove with inert absorbent.

Section 7 -- HANDLING AND STORAGE

STORAGE CATEGORY: DOL Storage Class IIIB

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE: Keep container closed when not in use. Transfer only to approved containers with complete and appropriate labeling. Do not take internally. Keep out of the reach of children.

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

PRECAUTIONS TO BE TAKEN IN USE: Use only with adequate ventilation. Avoid contact with skin and eyes. Avoid breathing vapor and spray mist. Wash hands after using. This coating may contain materials classified as nuisance particulates (listed "as Dust" in Section 2) which may be present at hazardous levels only during sanding or abrading of the dried film. If no specific dusts are listed in Section 2, the applicable limits for nuisance dusts are ACGIH TLV 10 mg/m3 (total dust), 3 mg/m3 (respirable fraction), OSHA PEL 15 mg/m3 (total dust), 5 mg/m3 (respirable fraction). Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. Exposure to lead dust or fumes may cause brain damage or other adverse health effects, especially in children or pregnant women. Controlling exposure to lead or other hazardous substances requires the use of proper protective equipment, such as a properly fitted respirator (NIOSH approved) and proper containment and cleanup. For more information, call the National Lead Information Center at 1-800-424-LEAD (in US) or contact your local health authority.

VENTILATION: Local exhaust preferable. General exhaust acceptable if the exposure to materials in Section 2 is maintained below applicable exposure limits. Refer to OSHA Standards 1910.94, 1910.107, 1910.108.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in Section 2. When sanding or abrading the dried film, wear a dust/mist respirator approved by NIOSH/MSHA for dust which may be generated from this product, underlying paint, or the abrasive.

PROTECTIVE GLOVES: Required for long or repeated contact.

EYE PROTECTION: Wear safety spectacles with unperforated sideshields.

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

PRODUCT WEIGHT : 8.46 lb/gal 1013 g/l **SPECIFIC GRAVITY:** 1.02 **BOILING POINT:** 212 - 213°F 100 -100°C
MELTING POINT: Not Available **VOLATILE VOLUME:** 96 % **EVAPORATION RATE:** Slower than ether
VAPOR DENSITY : Heavier than air **SOLUBILITY IN WATER:** N.A. **pH:** 7.0
VOLATILE ORGANIC COMPOUNDS (VOC Theoretical): 0.50 lb/gal 60 g/l Less Water and Federally Exempt Solvents 0.02 lb/gal 2 g/l Emitted VOC

Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable **CONDITIONS TO AVOID:** None known. **INCOMPATIBILITY:** None known.
HAZARDOUS DECOMPOSITION PRODUCTS: By fire: Carbon Dioxide, Carbon Monoxide **HAZARDOUS POLYMERIZATION:** Will not occur

Section 11 -- TOXICOLOGICAL INFORMATION

CHRONIC HEALTH HAZARDS: No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.

TOXICOLOGY DATA **CAS No.:** 9016-45-9 **Ingredient Name:** Nonylphenoxypoly(ethoxy)ethanol **LC50 RAT 4HR** Not Available **LD50 RAT** 1200. mg/kg

Section 12 -- ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: No data available.

Section 13 -- DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: Waste from this product is not hazardous as defined under the Resource Conservation and Recovery Act (RCRA) 40 CFR 261. Incinerate in approved facility. Do not incinerate closed container. Dispose of in accordance with Federal, State/Provincial, and Local regulations regarding pollution.

Section 14 -- TRANSPORT INFORMATION

No data available.

Section 15 -- REGULATORY INFORMATION

This product is not a DOT hazardous material. **BILL OF LADING (all sizes):** "Compound, cleaning and/or polishing"

SARA 313 (40 CFR 372.65C) SUPPLIER NOTIFICATION: No ingredients in this product are subject to SARA 313 (40 CFR 372.65C) Supplier Notification.

CALIFORNIA PROPOSITION 65: WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm.

TSCA CERTIFICATION: All chemicals in this product are listed, or are exempt from listing, on the TSCA Inventory.

Section 16 -- OTHER INFORMATION

This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR. The above information pertains to this product as currently formulated, and is based on the information available at this time. Addition of reducers or other additives to this product may substantially alter the composition and hazards of the product. Since conditions of use are outside our control, we make no warranties, express or implied, and assume no liability in connection with any use of this information.