



TECHNICAL DATA SHEET

GENERAL INFORMATION

VICTORY Floor Finish is a complex blend of the newest thermoplastic materials formulated to produce a durable high gloss surface. This new technology results in the most user friendly floor finish available today with properties such as; ease of application, outstanding leveling, high initial gloss, superior drying time and excellent slip resistance. While VICTORY Floor Finish is durable and glossy without buffing, the wet look can be achieved with any speed floor maintenance program.

VICTORY Floor Finish responds to low speed, high speed, and ultra high speed burnishing for the desired "wet look".

Recommended for use on vinyl asbestos, vinyl, reinforced vinyl, asphalt, and other types of resilient floors, in business, institutional and industrial establishments.

DIRECTIONS

1. Completely strip off all old floor finish using a Cello heavy duty stripper.
2. Remove all traces of stripper and old floor finish. Rinse floor 2 to 3 times with cool clear water. Allow floor to dry completely before coating the surface.
3. Pour VICTORY into a clean mop bucket. Use a clean finish mop free of all sizing. Saturate mop with floor finish and wring out until mop is damp, but not dripping.
4. Apply VICTORY in thin to medium coats. Apply multiple coats in order to produce the desired gloss.
NOTE: Since no two floors are the same, the number of coats applied will vary. To avoid streaking, hazing, or re-emulsification of the previous coat, allow appropriate drying time. Wait until the finish is dry to touch, then wait an additional 15 minutes before application of the next coat.
5. For optimum results burnish first coat using a white or other non-aggressive pad.

MAINTENANCE

1. Dry mop daily, using an untreated dust mop, to remove loose soil and grit.
2. To remove soil from the surface, mop or auto scrub with Cello's BEST YET! or LOW FOAM.
3. Spray buff with Cello's REDEEM, HI-PRODUCTION, or HI-BEAM to restore the gloss, or burnish as needed.
4. The occasional use of rejuvenators like SILVER STREAK, DRESS UP or HI-BEAM will enhance the appearance of the floor.
5. Scrub and recoat as required.

CAUTION: KEEP OUT OF REACH OF CHILDREN

SPECIFICATIONS

APPEARANCE: White Opaque Liquid

FRAGRANCE: Mild Acrylic

pH: 8.5 ± 0.5

COLOR UPON DRYING: Clear

GLOSS: Excellent

GLOSS RETENTION: Excellent

NON-VOLATILE SOLIDS: 22 ± 0.5

SCUFF RESISTANCE: Excellent

SOIL RESISTANCE: Excellent

WET ABRASION RESISTANCE: Excellent

DETERGENT RESISTANCE: Excellent

REMOVABILITY: Excellent

WATER SPOT RESISTANCE: Excellent

BURNISHABILITY: Excellent

REPAIRABILITY: Excellent

LEVELING AND RECOATABILITY: Excellent

COVERAGE:

FIRST COAT: 1500 ± 500 sq. ft. per gallon depending upon porosity of the floor

SUBSEQUENT COATS: 2000-3000 sq. Ft.

KEEP FROM FREEZING

**Cello Professional
Products**

1354 Old Post Road
Havre de Grace, MD 21078
Toll Free: 800-638-4850
www.cello-online.com

Z33 20110216