

DIMENSIONS FLOOR FINISH

TECHNICAL DATA SHEET

GENERAL INFORMATION

DIMENSIONS is the finish of choice for the floor care professional. DIMENSIONS FLOOR FINISH is a high solids, exceptionally durable and scratch resistant acrylic finish formulated to maintain its shine with less maintenance than most other finishes. DIMENSIONS dries remarkably brilliant upon initial application and will retain this "wet look" with a minimum of maintenance. In most cases, depending on traffic, daily dust mopping and damp mopping/auto scrubbing with weekly burnishing or spray buffing is all that's needed.

- "Wet Look" Initial Gloss
- Fast Drying
- Excellent Leveling
- Easy to Apply
- Outstanding Black Heel Mark Resistance
- Reduces Maintenance & Expensive Labor
- Excellent Detergent Resistance
- Maintain by any Spray Buffing or Burnishing
- Helps Prevent Static Build-Up in Retail Stores
- Highly Resistant to Scuffs & Scratches
- Prolongs Stripping Cycles
- Contains Ultra Violet Absorbers to Prevent Yellowing

Application for all floor surfaces both resilient and non-resilient. Use DIMENSIONS for supermarkets, department stores, shopping malls, airports, schools and public and private institutions.

DIRECTIONS

1. Completely strip off all old floor finish using Cello DIMENSIONS no rinse, low odor stripper.
2. Remove all traces of stripper and old finish. Rinse floor with cool clear water to remove any stripping debris. When using DIMENSIONS floor finish stripper, neutralizing is not necessary. Allow floor to dry completely before coating the surface.
3. Line the mop bucket with plastic liner to avoid contamination of floor finish. Use a clean finish mop free of all sizing. Saturate mop with floor finish and wring out until mop is damp, but not dripping.
4. Apply DIMENSIONS in thin to medium coats. Apply multiple coats in order to produce the desired gloss. Since no two floors are the same, the number of coats applied will vary. It is recommended that a minimum of 4 or 5 coats of DIMENSIONS be applied after floor has been stripped. For higher gloss durability and to provide an adequate wear layer additional coats should be applied within the first week of initial application. Floor should be scrubbed to remove soil prior to recoating.
NOTE: To avoid streaking, hazing, or re-emulsification of the previous coat, allow appropriate drying time. Wait until the finish is dry to the touch, then wait an additional 15 minutes before application of next coat.
5. For optimum results burnish first coat using a white or other non-aggressive pad.

MAINTENANCE

1. Dry mop daily, using a clean dust mop, to remove loose soil and grit.
2. To remove soil from the surface, mop or auto scrub with Cello's BEST YET!, LOW FOAM or NEUTRAGREEN.
3. Burnish with electric, battery or propane machine using appropriate pads.
4. Although not required, if your maintenance program includes an anti-slip, anti-static gloss rejuvenator, use Cello DIMENSIONS FLOOR RESTORATION TREATMENT.
5. Scrub and recoat as required using any cleaner listed in #2 above. Rinse and apply additional coats as required.

CAUTION: Eye irritant. Avoid contact with eyes. **FIRST AID:** In the event of eye contact, flush eyes with large amounts of clear water for at least 15 minutes. If irritation persists, seek medical attention.

SPECIFICATIONS

APPEARANCE: White opaque liquid

FRAGRANCE: Mild acrylic

NONVOLATILE SOLIDS: 22 ± 0.5

pH: 9.0 ± 0.5

SPECIFIC GRAVITY: 1.04

REPAIRABILITY: Excellent

DRYING TIME: See note above

LEVELING: Excellent

DETERGENT RESISTANCE: Excellent

SCUFF RESISTANCE: Excellent

SCRATCH RESISTANCE: Excellent

WATER SPOT RESISTANCE: Excellent

COVERAGE:

FIRST COAT: 1500 ± 500 sq. ft. per gallon depending upon porosity of the floor

SUBSEQUENT COATS: 2000-3000 sq. ft. per gallon

KEEP FROM FREEZING



**Cello Professional
Products**

1354 Old Post Road
Havre de Grace, MD 21078
Toll Free: 800-638-4850
www.cello-online.com

 CLASSIFIED BY
UNDERWRITERS LABORATORIES INC.®
AS TO SLIP RESISTANCE ONLY. 160S.

Z34 0205