



# TECHNICAL DATA SHEET

## GENERAL INFORMATION

LOW FOAM CLEANER is a heavy duty, non-butyl water based cleaning concentrate designed for use in automatic scrubbers equipped with proper floor pad or brush for cleaning and scrub/recoat maintenance. LOW FOAM's efficiency is derived from its outstanding wetting properties and unique no-rinse characteristics in a low foaming formulation.

Depending on the dilution selected, LOW FOAM can be used to clean the surface without adversely affecting the gloss of the floor finish; or at a more concentrated dilution, is effective in deep cleaning the floor for subsequent recoating of the floor finish.

### RECOMMENDED DILUTIONS

AUTOMATIC SCRUBBER:		
Light Soil	1/2 - 1 oz./gal.	1:128
Moderate Soil	2 oz./gal.	1:64
Heavy Soil	4 oz./gal.	1:32
<b>DAMP MOPPING</b>	1-2 oz./gal.	1:128 - 1:64
<b>SCRUB/RECOAT</b>	5-10 oz./gal.	1:20 - 1:13

## DIRECTIONS FOR USE

### CLEANING - Automatic Scrubber:

1. Dilute LOW FOAM, according to directions, in the detergent solution tank.
2. Release detergent; scrub and pickup simultaneously.

NOTE: Move at a slow to moderate speed, depending on soil conditions, so as to clean floor on first pass.

### SCRUB/RECOAT - Automatic Scrubber:

1. Dilute LOW FOAM, according to directions, in the detergent solution tank.
2. Release detergent over the desired area. Allow detergent to stand on the surface for a short period of time (30 seconds to 2 minutes, depending on how deeply it is desired to scrub).
3. Go over the area scrubbing with the appropriate pads or brushes (scrubbing or lighter) and pickup simultaneously. NOTE: Use a doodle bug and utility pad along baseboards and in corners where scrubber cannot reach.

IMPORTANT: Do not leave any liquid remaining on the floor.

4. Rinse area with cool, clean water. Allow to dry.
5. Floor is now ready for recoating with any Cello quality floor finish.

**OTHER USES:** LOW FOAM may also be used for damp mopping or scrubbing with a low speed machine. LOW FOAM may also be used on slate, concrete, cement, porcelain surfaces, plastic surfaces, and hand cleaning of walls at a dilution of 1 to 2 oz./ gal.

**WARNING:** Contains Potassium Hydroxide. Avoid contact with eyes and skin. **FIRST AID: SKIN:** Flush from skin immediately with plenty of water. Wash area with soap and water. If gotten on clothing, remove clothing immediately. Treat skin with soap and water in the affected area. If irritation persists, contact medical help. **EYES:** Flush eyes with plenty of water while propping lids open. Continue for 10 minutes. If irritation persists, contact physician. **IF SWALLOWED:** Do not induce vomiting. Call physician immediately. Drink large quantities of water.

## SPECIFICATIONS

**APPEARANCE:** Clear, purple liquid

**FRAGRANCE:** Green apple

**pH:** 13.25 ± .25

**VISCOSITY:** Water thin

**HARD WATER TOLERANCE:** Excellent

**BUTYL CELLOSOLVE CONTENT:** 0%

**FREEZER THAW STABILITY:** 3 cycles OK

**OVEN STABILITY 120°F:** Minimum 30 days

**Cello Professional  
Products**

1354 Old Post Road  
Havre de Grace, MD 21078  
Toll Free: 800-638-4850  
www.cello-online.com