



**BEST YET!
NEUTRAL CLEANER**

Z40

TECHNICAL DATA SHEET

GENERAL INFORMATION

BEST YET! is a specially formulated no-rinse neutral cleaner with a pleasant citrus fragrance. BEST YET! contains nonionic surfactants, water soluble degreasing agents, water softeners and buffering agents. It does an effective job of removing soil from coated floors without affecting the finish. Use BEST YET! for damp mopping, general light to moderate duty cleaning and removing heavy soils. BEST YET! is also recommended for use in automatic scrubbers. It's safe to use, and works effectively in both hard and soft water. It contains no harsh alkalis, phosphates, solvents or abrasives. BEST YET! can be used as an all purpose cleaner in a variety of applications including spray bottles, wall washers, sponges, etc.

RECOMMENDED DILUTIONS

MOPPING		
Light Soil	2 oz. per gallon	1:64
Moderate Soil	3-4 oz. per gallon	1:42 - 1:32
Heavy Soil	4-6 oz. per gallon	1:32 - 1:21
ROTARY MACHINE OR AUTO SCRUBBERS		
Light/Moderate Soil	1 oz. per gallon	1:128
Heavy Soil	2 oz. per gallon	1:64

DIRECTIONS

Dilute BEST YET! according to recommended dilutions into mop bucket with cool water. **DO NOT USE HOT WATER.** Mop floor using "figure eight" motion. Re-wet mop as necessary. Change water in mop bucket as solution becomes soiled. Rinsing BEST YET! should not be necessary, however a rinse is suggested when cleaning heavily soiled floors.

CAUTION: Eye irritant. Avoid contact with eyes.

FIRST AID: In the event of eye contact, flush eyes with large amounts of clear water for at least 15 minutes. If irritation persists, seek medical attention.

SPECIFICATIONS:

APPEARANCE: Clear yellow liquid

FRAGRANCE: Citrus

pH: 7.0-8.0

DILUTION: As recommended above

VISCOSITY: Same as water

FLASH POINT: None

SOLUBILITY: Complete

SHELF LIFE: Minimum 1 year from date of sale

FREEZE/THAW STABILITY: Minimum 3 cycles (A.S.T.M. Test D-3209-82)

Cello Professional Products

1354 Old Post Road
Havre de Grace, MD 21078
Toll Free: 800-638-4850
www.cello-online.com



CLASSIFIED BY
UNDERWRITERS LABORATORIES INC.®
AS TO SLIP RESISTANCE ONLY. 160S.

Z40 0205